



# Idrosan Semilucida

## Sanitising water-based Enamel anti-mould

CODE 1011 / 1012



### COLOUR

36 dyes from colours chart – more than 170 colourings from Plastimur swatch book. Moreover, with the new tintometer colorization system, it is possible to obtain countless paints.

### PACKAGING

Drums litographed of lt 4 and 13

### STORAGE

12 months at least in its original packaging far from low and high temperatures

### CHARACTERISTICS

It is a wall cladding water-based enamel very high quality, sanitising and anti-mould, semi-gloss look, washable, covering, excellent degree of whiteness, suitable for both internal and external areas where high performance is requested; it is composed of emulsions, micronized charges, specific admixtures against moulds and fungus, so it contrasts the micro-organism present on the surfaces and at the same time prevents the growth of them.

### PREPARATION AND APPLICATION

**New surfaces:** substrates have to be fine-finished, cured and dry; apply one coat of fixative ALBURESIN diluted with water in ratio 1:5 up to 1:10, basing on the substrate's absorption and let it dry 5/6 hours. Apply through brush or roller two or more coats of water-painting diluted with 15-30% of water, with an interval between the coats of 5-6 hours.

**Old surfaces contaminated:** apply in uniforming way PREVEN R50 on all the surfaces you want to treat to sterilize, and wait for the product's efficacy for about 12 hours. Clean removing blackened parts; apply ALBURESIN in ratio 1:5 up to 1:10 and let it dry 5/6 hours; apply the water-painting diluted with 15-30% of water, with an interval between the coats of 5-6 hours.

rev. 03 del 30.09.2016

### CONSUMPTION

About 0,120-0,160 Lt / mq

### TECHNICAL DATA

#### PRODUCT IDENTIFICATION DATA

<b>Colour</b>	36 dyes from colours chart – more than 170 colourings from Plastimur swatch book. Moreover, with the new tintometer colourization system, it is possible to obtain countless paints.
<b>Density</b>	1,400 kg/lt
<b>Brilliance</b>	Semi-gloss
<b>Dilution</b>	with water 15-30%
<b>Drying for touch</b>	1-2 hours
<b>Drying in depth</b>	24-36 hours
<b>Application temperature</b>	from +5°C to +30°C
<b>Flammability</b>	Non-flammable

### ITEM SPECIFICATION

Decoration and protection of wall surfaces with water-based painting of very high quality, sanitising and anti-mould, semi-gloss look, washable, covering, excellent degree of whiteness, suitable for both internal and external areas, IDROSAN SEMILUCIDA (semi-gloss) of Plastimur s.r.l., composed of emulsions, micronized charges, specific admixtures against the moulds and fungus, so it contrasts the micro-organism present on the surfaces and at the same time prevents the growth of them.