



Albusil Fissativo

Fixative for mineral-base coatings

CODE 2003



COLOUR

Straw Yellow

PACKAGING

Drums in PVC It 5-10-16

STORAGE

12 months, well-sealed in its original packaging, far from low and high temperatures.

CHARACTERISTICS

ALBUSIL FISSATIVO MINERALE is a fixative with a high penetrating power, ready to use, in straw yellow colour; it is composed of a mix in silicate polymers and specific admixtures. It is suitable for substrate treatment before mineral coatings application. Also employable to uniform the substrates absorption and consolidate the surface. Thanks to its high penetrating power it doesn't create film-effects.

APPLICATION PROCEDURE

SUBSTRATES PREPARATION

The substrate must be clean, dry, and free from detaching parts, oils, greases. Any eventual painting or synthetics coating must be completely removed before the product application.

PREPARAZIONE DEL PRODOTTO

The product is ready to use.

APPLICATION

Apply the product at temperatures between +5°C and +30°C, by means of brush, roller or spray in only one coat. Eventual plaster patches must be perfectly dry and cured.

rev. 03 del 30.09.2016

CONSUMPTION

The performance depends on the substrates porosity and absorption, normally with an average consumption of 0,200 lt/mq.

TECHNICAL DATA

PRODUCT IDENTIFICATION DATA

| | |
|-----------------|--------------|
| Appearance | Liquido |
| Colour | Straw Yellow |
| Specific Weight | 1,200 kg/lt |

WARNINGS

Do not employ on wet substrates, eventual plaster patches must be perfectly dry and cured; protect the parts not to treat. Use protective gloves and glasses to handle the product. Protect the glasses carefully: in case of staining, wash immediately with clean water.

VOCE DI CAPITOLATO

Preparation of the surfaces treated with finishing mineral coating, with ALBUSIL FISSATIVO Plastimur s.r.l, made of a mix in silicate polymers and specific admixtures, applied with brush, roller or spray, with an average consumption of 0,200 lt/mq.