



# Albusil Vernice

Waterproofing and painting for surfaces

CODE 2006



<b>COLOUR</b>	Transparent
<b>PACKAGING</b>	Bottles lt 1 and Drums lt 5 / 10 / 20 / 25
<b>STORAGE</b>	24 months, well-sealed in its original packaging, far from low and high temperatures.

### CHARACTERISTICS

Albusil Vernice is a thermoplastic product, based on acrylic resins dissolved in solvent, characterized by an internal plasticizing and fast drying. This is a low viscosity product with high penetrating power, suitable as waterproofing, consolidating and painting agent, for printed floorings, cotto tiles, stone etc.

### APPLICATION FIELDS

Thanks to its waterproofing, consolidating, weatherproof characteristics, being resistant to alkaline agents, this product is suitable for the painting and protection of the following substrates: cotto tiles, stone floorings, cement bricks, industrial floorings, concrete surfaces, printed floorings etc.

### APPLICATION PROCEDURE

#### SUBSTRATES PREPARATION

Before the application, substrates must be solid, dry, free of oils, greases, paintings and salt efflorescence. The surface cleaning must be done through washing with clean water, preferably under pressure, or through accurate brooming and dedusting system.

#### PRODUCT PREPARATION

The product is ready to use.

#### PRODUCT APPLICATION

Apply the product in one or more coats, uniforming it using brush, roller, or spray.

rev. 03 del 30.09.2016



Brush application of Albusil vernice

## APPLICATION AND TECHNICAL DATA

Appearance	Liquid
Colour	Transparent or Coloured
Density	0,900 kg/lit
Application Temperature	from +5°C a +30°C
Drying Time	physical drying, because of the solvent evaporation.
Flammability	Flammable

## CONSUMPTION

The performance depends on the substrates porosity and absorption, normally with an average consumption of 0,250 Lt/mq.  
In case of printed floorings 0,100-0,250 Lt/mq..

## WARNINGS

Flammable and volatile product; do not smoke and do not use flames during the usage. If apply it in closed location, air the place. For the handling of the product it is recommended to use protective gloves, glasses and clothes, and adequate mask to protect yourself from the inhalation.

In case of swallowing or contact with eyes turn to medical treatments.

Do not release the product and its container to the environment. Close always the Albusil Antisale drums carefully, to avoid that the product acts with the carbon dioxide present in the air and so loses its efficacy

## ITEM SPECIFICATION

Painting and consolidating treatment of absorbent substrates such as: cement bricks, cotto tiles, stone floorings, printed floorings, industrial floorings, concrete surfaces etc., based on acrylic resins dissolved in solvent, characterized by an internal plasticizing and fast drying. Colourless, ready to use, Albusil Vernice of Plastimur s.r.l, applied with brush, roller or spray, with an average consumption of 0,250 lt/mq.