



# Rasostuck

Lime-Marmorino Coating internal/external

CODE 6001 - 6002



### COLOUR

16 dyes from colours chart.  
Dyes apart from the chart can be requested.

### PACKAGING

Drums litographed of kg 6-25

### STORAGE

12 months, well-sealed in its original packaging far from high and low temperatures.

## CHARACTERISTICS

It is a coloured coating in mineral paste, natural, transpiring and ecological, ready to use, conceived to obtain specular and smoothed polychrome coatings, typical of ancient decoration traditions. It is composed of lime, air binders, selected aggregates, pigments and specific admixtures. Conceived in particular for internal and external finishings, renovation of historical buildings and new buildings, where you want to turn back to the ancient decoration traditions.

## APPLICATION PROCEDURE

### SUBSTRATES PREPARATION

Substrates have to be preferably clean, solid and dry, perfectly flat and finished, any eventual irregularity must be removed previously with cementitious smoothing. On gypsum substrates or plasterboard panels, for a good bonding it is necessary a basing coat of RASOGRESS of Plastmur s.r.l. In case of cured substrates it is suggested to brush and damp them before the application.

Do not apply on substrates treated with synthetic coatings, damaged or inconsistent substrates. Remove crumbly parts, oil, paints traces or paints previously treated.

### PRODUCT PREPARATION

Product in paste ready to use. Amalgamate again before the application.

### APPLICATION

It is suggested to apply the product in two or three coats, after the RASOGRESS application in case of surfaces difficult to treat. Apply the first coat with Inox trowel in a thickness of 1 mm, being careful in obtaining a uniform thickness and let it dry for 4/5 hours; apply the second coat basing on the effect you want to obtain, smoothing tightly removing the excess material; apply the third coat like the second one to uniform basing on the uniformity of the effect you want to obtain, then press and polish with the same clean trowel, until you obtain the desired effect.

rev. 03 del 30.09.2016

**CONSUMPTION**

1,0-1,2 kg/mq depending on the substrate.

**TECHNICAL DATA****PRODUCT IDENTIFICATION DATA**

<b>Appearance</b>	Pasty
<b>Colour</b>	White / coloured
<b>Specific weight</b>	1,670 kg/lt

**WARNINGS**

Do not apply in strong windy conditions, heavy rain, or direct sun.

Do not apply on frozen surfaces or thawing conditions or at the risk of freezing.

Protect the parts not to dirty.

In case of extended surfaces consider some adequate interruptions next to joints or waterspouts.

Alkaline product, protect eyes, hand and the skin from a direct contact during the application.

In winter periods it is necessary to protect the coating, since some superficial white efflorescences could form (carbonation = free lime into the binders), due to heavy rain, high humidity rate, or application effectuated before or during low temperatures. This phenomene coul happen before the coating's curing is completed (+/- 28 days).

**ITEM SPECIFICATION**

Decoration and protection of internal and external surfaces, with smooth coloured mineral finishing in lime paste, ready to use, RASOSTUCK of Plastimu s.r.l., composed of lime, air binders, selected aggregates, pigments and specific admixtures. To apply manually in two or three coats: the first one with inox trowel in a thickness of 1 mm, the second one in small patches smoothing tightly and removing the excess material; apply the third coat like the second one to uniform basing on the uniformity of the effect you want to obtain, then press and polish with the same clean trowel. Average consumption of 1,0-1,2 kg/mq.