



PLASTIMUR

Pittura per piscina

Waterpainting elastomeric and hydrophobic at low thickness

CODE 1019 - 1020



COLOUR

White, light blue or light colours from chart

PACKAGING

Drums litographed of lt 4 and 13

STORAGE

12 months at least in its original packaging far from low and high temperatures.

CHARACTERISTICS

PITTURA PER PISCINA is an elastomer product at low thickness for the protection and waterproofing of external surfaces composed of specific resins, micronized aggregates, pigments and specific admixtures.

APPLICATION FIELDS

Thanks to its bonding and elasticity characteristic this product is employed for the painting of swimming pools, water tanks, internal and external surfaces, faced concrete etc. Not for food use.

APPLICATION PROCEDURE

SUBSTRATES PREPARATION

Substrates have to be fine-finished, cured, perfectly clean, in good conditions, with no detaching parts, oil, grease, dust, humidity, saltpetre or moulds traces. Eventual crumbling surfaces need to be previously consolidated before the product application.

PRODUCT PREPARATION

Dilute the product with 30% of clean water for the first coat, 40% for the second one, mixing the product with a drill at a low speed rotations, obtaining a dough homogeneous.

PRODUCT APPLICATION

Apply in two or more coats, through brush, wool roller or spray, after application of insulating fixative ALBURESIN, after at least 12-24 hours in normal conditions of temperatures and humidity. Apply the product at temperatures between +5°C and +30°C. Do not apply with UR higher than 85%.

CONSUMPTION

About 0,200 - 0,300 lt / mq

TECHNICAL DATA

PRODUCT IDENTIFICATION DATA

Consistency	Liquid dense
Colour	White, light blue or light colours from chart
Density of the paste	1,240 kg/lt
Brilliance	Opaque

APPLICATION DATA

Dilution ratio	30% for the first coat 40% for the second one
Waiting time between coats	6/8 hours
Time to drying for touch	about 2 hours
Drying time	24-36 hours basing on the environmental temperature and substrate's absorption.

FINAL PERFORMANCE

Resistance to chemical attacks: excellent to atmospheric agents and smog.

ITEM SPECIFICATION

Decoration and protection of surfaces as: water tanks, pools, internal and external surfaces, faced concrete etc, with elastomer painting in water solution, PITTURA PER PISCINA of Plastimur s.r.l., composed of high elasticity resins. This painting is to apply in two or more coats, diluting with 30% of clean water, with an average consumption of 0,200-0,300 lt/mq.